

TECHNICAL DATA SHEET FOR

ODOUR-LESS EASYWASH

Description	:	Odour-less EasyWash is a super premium acrylic paint with superior stain resistance and easy stain removal. It is specially formulated with “Green” ingredients to limit air pollutants and other environmental impacts. It has extremely low odour during application and drying and is ideal for the painting of commercial and residential areas with high human traffic
Type	:	Acrylic polymer emulsion paint for interior use
Colour	:	As per color card
Finish	:	Soft sheen
Uses	:	Recommended for all interior masonry surfaces
Features	:	<ul style="list-style-type: none">• Extremely low odour during application and drying• Ammonia-free• Alkyl Phenol Ethoxylate (APE) surfactant free, formaldehyde free• Non-toxic, does not contain lead, mercury and heavy metals• Excellent stain resistance to common household stains• Good washability• Elegant soft sheen finish• Long lasting colors• Fungus resistant• Alkali resistant• Easy application• Excellent flow and leveling• Excellent coverage and hiding power• Environmentally friendly paint certified under the Singapore Green Building Product Certification Scheme

APPLICATION DATA

Method	:	Roller or brush
Theoretical Coverage	:	13 m ² / litre (based on 30 microns DFT)
Dilution	:	No dilution is necessary for best performance
Surface Preparation	:	Ensure surface is clean, dry and stable using the following suggested surface treatments: <ul style="list-style-type: none">• Moisture :There must not be any water residue on the surface of the substrate. Moisture must be <4% (Sovereign moisture master) before application

ODOUR-LESS EASYWASH

- **Unstable matter** : Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable
- **Contaminants** : Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry
- **Fungus and Algae** :Wash the affected area to remove unstable matters and micro-organisms. Apply Anti-Fungus Solution and leave on for at least 2 hours
- **Hairline cracks** :Fill cracks with suitable exterior grade water-resistant putty or filler

Drying Time	:	Surface Dry - 30 minutes at 30°C Hard Dry - 2 hours at 30°C
Over coating Time	:	2 hours based on normal conditions
Recommended Painting System	:	1 coat of 5101 Odour-less Sealer or Vinilex 2000 Wall Sealer 2 coats of Odour-less EasyWash
Cleaning	:	All equipment should be cleaned with water immediately after use

GENERAL INFORMATION

Solid Content	:	54 ± 2% by weight (based on white colour)
Specific Gravity	:	1.31 ± 2% kg / litre (based on white colour)
Packing	:	1 litre and 5 litres
Storage	:	Store in a tightly sealed container in a cool dry place
Shelf Life	:	Up to 24 months in a tightly sealed container
Precaution	:	Ensure good ventilation during application and drying of paint Avoid direct contact with sensitive skin. Use appropriate personal protective equipment Refer to the product Safety Data Sheet for more information

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

Enquiries / Contact Details : **Customer Service**
6265 5355 (Main Line)
6264 1603 (Fax)
www.nipponpaint.com.sg